APPLICATION FOR PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA

	Date of filing in State Engineer's Office
]	Returned to applicant for correction SEP 2 9 1995
(Corrected application filed
]	Map filed OCT 0 5 1995 under 61509
	The applicant Atlandia Design and Furnishings, Inc. for the project known as "Bellagio" 3260 South Industrial Road of Las Vegas Street and No. or P.O. Box No. City or Town
	Nevada 89109 , hereby make application for permission to appropriate the public
	waters of the State of Nevada, as hereinafter stated. (If applicant is a corporation, give date and place of incorporation; if a
,	copartnership or association, give names of members.)
	Incorporated July 9, 1979; Incorporated in the State of New Jersey
)	. The shallow aquifer containing the perched
	1. The source of the proposed appropriation is in the shallow aquifer containing the perched underground nuisance water at the Name of stream, lake, spring, underground or other source Bellagio project in Clark County, Nevada; Las Vegas Basin (see attached map).
	2. The amount of water applied for is ***********************************
	(a) If stored in reservoir give number of acre-feet Not Applicable
	3. The water to be used for Recreational use (see "No.12 Remarks") Irrigation, power, mining, manufacturing, domestic, or other use. Must limit to one use.
	4. If use is for:
	(a) Irrigation, state number of acres to be irrigated Approximately 10 acres of landscaping
	(b) Stockwater, state number and kinds of animals to be watered Not Applicable
	(c) Other use (describe fully under No. 12. "Remarks" Water Feature(s)
	(d) Power:
	(1) Horsepower developed Not Applicable
l	(2) Point of return of water to stream Not Applicable
	5. The water is to be diverted from its source at the following point SW ¹ / ₄ NE ¹ / ₄ SECTION 20, TOWNSHIP 21S,
	BEARING: S 18°01'19" E 1425.86' FROM THE NORTHWEST CORNER OF THE NE
	survey, and by course and distance to a section corner. If on unsurveyed land, it should be so stated. SECTION 20 (POINT OF DIVERSION ''WELL #17'')
	6. Place of use <u>Within Project Area known as Bellagio</u> , see attached map dated September 6, 1995. All Describe by legal subdivision. If on unsurveyed land, it should be so stated.
	September 6, 1995. All Describe by legal subdivision. If on unsurveyed land, it should be so stated. Within the following $''\frac{1}{4}-\frac{1}{4}''$ Sections:
NE ¹	The state of the s
NW社 SE社	NET SECTION 20, TOWNSHIP 21 S., RANGE 61 E., M.D.M., CLARK COUNTY, NEVADA
SWing NEi	NE ¹ / ₄ SECTION 20, TOWNSHIP 21 S., RANGE 61 E., M.D.M., CLARK COUNTY, NEVADA SE ¹ / ₄ SECTION 20, TOWNSHIP 21 S., RANGE 61 E., M.D.M., CLARK COUNTY, NEVADA
NW &	SE SECTION 20, TOWNSHIP 21 S., RANGE 61 E., M.D.M., CLARK COUNTY, NEVADA
SW⅓	
)	7. Use will begin about January 01 and end about December 31 month and Day, of each year. 8. Description of proposed works. (Under the provisions of NRS 535.010 you may be required to submit plans and
	specifications of your diversion or storage works.) Drilled well with pump and motor.
	State manner in which water is to be diverted, i.e. diversion structure, ditches and

flumes, drilled well with pump and motor, etc.

9.	Estimated cost of works Unknown at this time.	
0.	Estimated time required to construct works. Unknown at this time. If well completed, descr	ibe works.
1.	Estimated time required to complete the application of water to beneficial use "Be1 completion estimated at March 1998.	lagio" project
	Remarks: For use other than irrigation or stock watering, state number and type of consumptive use:	
	To be used for approximately 10 acres of landsc	ape irrigation and
	approximately 11 acres of surface area water fe	
	"Bellagio" project	
	PETER T. SMITH, Executive Vice P	resident
	By S/ Peter T. Smit 3260 South Indus	n trial Road
on	npared ds/bk cl/cms Las Vegas, Nevad	a 89109
rot	tested	
	APPROVAL	
	APPROVAL OF STATE ENGINEER	
	This is to certify that I have examined the foregoing application, and do hereby growing limitations and conditions:	ant the same, subject to the
	right obtained under this permit will be dependent upon the a	mount of water actual
ce	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of to caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source. This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in near the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2) amount of water to be appropriated shall be limited to the amount which can be applied and the content of the amount which can be applied the content of the c	ea of the place of us the rise of groundwat guarantee the long te ce. for measuring depth is two (2) inch opening wells. the discharge pipelipe kept of water place it to beneficial use, and not to not to exceed 246.0
ce	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of to caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source. This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in near the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2)	ea of the place of usche rise of groundwate guarantee the long terms. for measuring depth is two (2) inch opening wells. the discharge pipelities kept of water placed to beneficial use, and not to not to exceed 246.0
ксе	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of to caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source. This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2) amount of water to be appropriated shall be limited to the amount which can be applied and the control of the control	ea of the place of us the rise of groundwat guarantee the long te ce. for measuring depth s two (2) inch opening wells. the discharge pipelipe kept of water place it to beneficial use, and not to not to exceed 246.0
or	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of to caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source. This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in the near the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2) amount of water to be appropriated shall be limited to the amount which can be applied to the accuracy of the provided control of the contr	de a of the place of us the rise of groundwat guarantee the long te ce. I for measuring depth set two (2) inch opening wells. The discharge pipelice kept of water place it to beneficial use, and not to not to exceed 246.0 June 17, 1998
or	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of to caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source. This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in near the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2) amount of water to be appropriated shall be limited to the amount which can be applied to the accuracy of the prosecuted with reasonable diligence and be completed on or before	ea of the place of us the rise of groundwat guarantee the long te ce. for measuring depth s two (2) inch openin ring wells. the discharge pipeli be kept of water place i to beneficial use, and not to not to exceed 246.0 June 17, 1998 July 17, 1998
/or	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of to caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source. This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in near the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2) amount of water to be appropriated shall be limited to the amount which can be applied acced. 0.65 cubic feet per second. but acre-feet annually.	the rise of groundwate guarantee the long terms of groundwate guarantee the long terms of the ce. for measuring depth as two (2) inch opening wells. the discharge pipelism we kept of water place in the discharge pipelism of the central use, and not to not to exceed 246.0 June 17, 1998 July 17, 1998 July 17, 1998 July 17, 2001
roc	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of to caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source. This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in near the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2) amount of water to be appropriated shall be limited to the amount which can be applied acced. 0.65	ea of the place of us the rise of groundwat guarantee the long te ce. for measuring depth s two (2) inch opening wells. the discharge pipelice kept of water place it to beneficial use, and not to not to exceed 246.0 June 17, 1998 June 17, 2001 July 17, 2001
vce	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of to caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source. This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this. The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in near the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2) amount of water to be appropriated shall be limited to the amount which can be applied accurate feet annually. The must be prosecuted with reasonable diligence and be completed on or before	ea of the place of us the rise of groundwat guarantee the long te ce. for measuring depth s two (2) inch opening wells. the discharge pipelice kept of water place it to beneficial use, and not to not to exceed 246.0 June 17, 1998 July 17, 1998 July 17, 2001 July 17, 2001
/or /or pp roc	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of to caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source. This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in near the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2) amount of water to be appropriated shall be limited to the amount which can be applied accurate. C.65 cubic feet per second. but accrefeet annually. In the state Engineer of Nevada, have hereum for beneficial use filed. In testimony whereof, I, R. M. State Engineer of Nevada, have hereum for beneficial use filed. In testimony whereof, I, R. M. State Engineer of Nevada, have hereum for beneficial use filed.	to set my hand and the seal of my the rise of groundwate guarantee the long te ce. for measuring depth as two (2) inch opening wells. the discharge pipelities kept of water place in the discharge pipelities and not to mot to exceed 246.0 June 17, 1998 June 17, 2001 N/A ICHAEL TURNIPSEED, P. to set my hand and the seal of my
voce Vor Proce Proce Var Vom	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of t caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in near the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2) amount of water to be appropriated shall be limited to the amount which can be applied acre—feet annually. It must be prosecuted with reasonable diligence and be completed on or before	to set my hand and the seal of my The case of the place of use the rise of groundwate guarantee the long terms of the case. The case of groundwate guarantee the long terms of the case
Vor Proc App Troc Mar Com	This permit is issued subject to the provisions of NRS 5 and based on the particular hydrologic conditions in the are The water to be diverted under this permit is a result of to caused by secondary recharge and therefore does not provide or availability for continuous use of this water from this source. This well shall be equipped with a two (2) inch opening water. A dedicated monitoring well can be used in lieu of this The State Engineer shall approve the placement of any monitor. A totalizing meter must be installed and maintained in near the point of diversion and accurate measurements must be (CONTINUED ON PAGE 2) amount of water to be appropriated shall be limited to the amount which can be applied accurate. C.65 cubic feet per second. but accrefeet annually. In the state Engineer of Nevada, have hereum for beneficial use filed. In testimony whereof, I, R. M. State Engineer of Nevada, have hereum for beneficial use filed. In testimony whereof, I, R. M. State Engineer of Nevada, have hereum for beneficial use filed.	to set my hand and the seal of my The case of the place of use the rise of groundwate guarantee the long terms of the case. The case of groundwate guarantee the long terms of the case

(O)-2145 (Rev. 9-89)

Page 2 61525

(PERMIT TERMS CONTINUED)

to beneficial use. The totalizing meters and any monitoring wells must be installed before any use of water begins, or before the Proof of Completion of Work is filed.

The place of use of this permit is limited to the area described within the place of use which is called the Bellagio Project.

The depth of the well under this permit shall not in any case exceed sixty feet in depth nor shall the well penetrate any confining layer below this shallow aquifer.

A monthly report shall be submitted to the State Engineer within 10 days from the end of each month which shall include the amount of water pumped from each well, the use of the water and the depth to water in this well or any monitoring well.

Water quality samples shall be taken from each well on a quarterly basis, analyzed for total dissolved solids (TDS), pH and sulfates (SO_4), and reported to this office along with the appropriate monthly report.

This permit does not extend the permittee the right of ingress and egress on public, private or corporate lands.

The issuance of this permit does not waive the requirements that the permit holder obtain other permits from State, Federal and local agencies.

The total combined duty of water under Permits 61509, 61510, 61511, 61512, 61513, 61514, 61515, 61516, 61517, 61518, 61519, 61520, 61521, 61522, 61523, 61524, 61525, 61526, 61527, 61528, 61529, 61530, 61531, 61532, 61533, 61534, 61535, 61536, 61537, 61538 and 61539 shall not exceed 246.0 acre-feet annually.

The State retains the right to regulate the use of the water herein granted at any and all times.

The state of the s